



# Ceramic Coating

## 39901

Technical Data

January 2021

3M Part Numbers	3M Part Descriptor
33901	1 Kit, 4 Kits/Case

### Product Description

3M™ Ceramic Coating is a proprietary paint coating treatment for vehicles which is professionally applied to provide enhanced depth and luster to an automotive finish as well as a slick surface for easy maintenance. Excellent water beading effect provides a just polished look that is durable in a variety of conditions for up to five years with proper care & maintenance.

#### Kit Contains:

- 1 – 40 mL bottle of Ceramic Coating
- 1 – Applicator Block
- 8 – Applicator Cloths

Features, Advantages, Benefits	Feature	Advantage	Benefit
	Protective coating developed using proprietary 3M technology	Delivers a durable, protective layer that will bead water and provide extreme slickness for five years when properly maintained	Keeps your car looking cleaner with a deep, glossy appearance that is easier to maintain
	Kit contents will allow for the coating of two full sized vehicles	Chemical resistance against road salt, harsh detergents, acid rain and other environmental contaminants	Slick surface finish makes cleaning & maintenance easier & easier tape placement
	Unique, reusable applicator block with impervious backing and fitted applicator cloths	Easy to apply formula that cures in four hours, allowing for fast turnaround	Contaminants like tree sap, bug spots, bird droppings and brake dust can be removed easier than non-coated surfaces
	Versatile coating for multiple surfaces	Can be used to protect paint, film, vinyl, trim, headlights, and wheels	Return the vehicle to the customer on the same day, freeing up valuable shop space for the next job

# 3M™ Ceramic Coating

39901

## Product Uses

3M™ Ceramic Coating is designed to protect automotive paint, trim, film, vinyl wraps, and wheels. For glass applications, use with 3M™ Glass Pre-Treatment.

## Performance Properties

NOTE: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

<b>Chemistry</b>	Siloxane Polymer Blend
<b>Appearance</b>	Clear, colorless liquid
<b>Cure Time</b>	~4 hours

## Directions for Use

*Attention: Wear protective gloves and eye/face protection. Always apply **3M™ Ceramic Coating** in a clean environment free of dirt/dust and away from wash bays, overspray, or other vehicles being paint corrected.*

1. Wrap applicator cloth around foam applicator so the elastic band wraps completely around the block, exposing the 3M™ logo on the back side of the block. Tilt bottle and apply ~12-16 drops of 3M™ Ceramic Coating to the applicator cloth.
2. Start with 3M™ Ceramic Coating on the roof of the vehicle working your way down the vehicle as you go. Limit application area to approximately 2' x 3' (60cm x 90cm) section. Apply 3M™ Ceramic Coating in a north/south and east/west, cross hatch pattern. Ensure no area is left uncoated. Limit application time to approximately 1-2 minutes per 2' x 3' (60cm x 90cm) section.
3. Allow coating to dwell on the surface for 2-5 minutes. Level coating using a clean microfiber cloth. View panel at different angles to ensure the coating has been properly leveled and a uniform appearance is achieved. Avoid leaving high spots or excess coating on the surface. Avoid applying pressure to the surface of the vehicle with the microfiber cloth, this could cause scratches to the surface.
4. Repeat Steps 1-3 over rest of vehicle, applying ~8 drops of 3M™ Ceramic Coating to the applicator cloth at the start of each new section. Change applicator cloth after applying 3M™ Ceramic Coating to half of an average sized vehicle. Use a new, clean, microfiber cloth when leveling excess material. Re-using applicator cloths or microfiber leveling cloths could result in cured coating scratching the paint surface.
5. After applying 1st coat of 3M™ Ceramic Coating, wait 30-60 minutes before proceeding to the 2nd coat.
6. Apply 2nd coat of 3M™ Ceramic Coating over entire surface of the vehicle by following Steps 1-4.
7. Keep vehicle out of contact of water for at least 4 hours.

# 3M™ Ceramic Coating

39901

---

## Storage and Handling

For best performances, apply to surfaces above 60°F (16°C). Optimum storage conditions are 22°C (72°F) and 50% relative humidity. Cap immediately after each use.

---

## Precautionary Information

Before using this product, please reference Product Label and/or Safety Data Sheet for Health and Safety Information. Note: Laws controlling the acceptable amounts of Volatile Organic Compounds (VOCs) vary by state, and in some cases by locality. For surface preparation and clean-up activities, consult federal, state and local regulations regarding use of products containing VOCs in your area.

---

## Technical Information

The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

---

## Product Selection and Use

Many factors beyond 3M's control and uniquely within the user's knowledge and control can affect the use and performance of a 3M product in a particular application.. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product in accordance with all applicable instructions and with appropriate safety equipment, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

---

## Warranty, Limited Remedy and Disclaimer

Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement or repair of the 3M product or refund of the purchase price. Warranty claims must be made within one (1) year from the date of 3M's shipment.

# 3M™ Ceramic Coating

39901

---

## Limitation of Liability

Except for the limited remedy stated above, and except to the extent prohibited by applicable law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

---

## Disclaimer

3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and other limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, death, or property damage. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit [www.3M.com](http://www.3M.com).<sup>[1]</sup>



Automotive Aftermarket Division  
3M Center, Building 0223-6-S-07  
St. Paul, MN 55144-1000  
1-877-666-2277 (1-877-MMM-CARS)  
[3MCollision.com](http://3MCollision.com)

3M is a trademark of 3M Company.  
Printed in U.S.A. © 3M 2021 All rights reserved (01/21)