

Transit Wrap Film

Fellers Black Label Transit Wrap Film is a unique, 4-mil product featuring a robust face film with a removable solvent-based adhesive. This product is best used for short-term wraps including taxi-cabs, buses, or other times when shorter-term applications are required. The film has the unique feature that it is conformable enough to do short-term wraps but can also be used for flat applications and layered up to 4 times. This makes it also suitable for short-term wall wraps or wall stickers. The product can be laminated with a calendared laminate or installed without laminate. While cold lamination is possible, Fellers recommends heat assist when possible, not to exceed 115 degrees.

Product Description	Transit Wrap Film
Film	
Film Type	Calendared Vinyl
Film Thickness (mils) ASTM-D 1593	4 mil; 100 micron (+/- 10%)
Gloss Level	≥ 60
Elongation (%) ASTM D882	MD ≥ 140
Dimensional Stability (% shrinkage) ASTM D1004	MD ≤ 0.040"
Adhesive	
Adhesive Type	Solvent
Adhesive Thickness	1.55-1.75 mil; 39-44 micron
Adhesive Color	Clear
Peel Strength on Glass: 15 min typical value (lbs/in / N/25m)	2.5
Peel Strength on Glass: 24 hrs typical value (lbs/in / N/25m)	3.5
Liner	
Liner Weight (lbs / gsm)	90 / 140
Liner Type	DSPE ¹
Liner Thickness (mils / microns)	7 / 178
Release Force @ 300" / min (g/2") ASTM D-1000	24 - 36
Performance Guidance	
Application Temperature	50 to 75 °F
Service Temperature	-40 to 175 °F
Shelf Life	1 year
Storage Temp / Rel. Humidity	70 °F / 50%
Outdoor Durability	3 years †
Removability	Clean with heat
Watercraft Applications	Not recommended

Disclaimer

All data provided in this document is based upon tests executed by Fellers or their manufacturing partners and determined to be reliable information. Results may represent an average and any minimum or maximum values provided should be considered as a recommendation based on average circumstances. In the end, it is up to the end user to determine at their risk if the product is right for the desired application and outcome. These settings do not provide or imply a guarantee of the products use, outdoor durability, removability, or printability. In general, non-vertical applications can result in a reduced performance of 50% or more. This information is subject to change at any time without notice.

Notations:

† Typical weather conditions, Vertical mounted, Unprinted. Overall durability of the product is application dependent and should be considered the shortest-term durability of any of the finished sign components.

MD - Machine Direction
¹ DSPE - Double-Sided PE



6566 East Skelly Drive, Tulsa, OK 74145 | (800)654.8405 | fellers.com