

## STANDARD GRADE APPLICATION TAPE

4075RLA®

4075RLA® Conform Series® application tape is standard weight saturated paper coated with a high tack rubber adhesive designed specifically as a premasking of small and mid-sized die cut or prespaced vinyl and printed graphics. 4075RLA® features RLA® technology with improved adhesion to paper or film release liners.

### PHYSICAL SPECIFICATIONS

Adhesive	<b>Rubber-based</b>
Color	<b>White/Translucent</b>
Caliper facestock	<b>100-113 microns (4.0 -4.5 mils)</b>
Caliper facestock + adhesive	<b>125-138 microns (5.0 - 5.5 mils)</b>
Adhesion to Steel*	<b>18 - 20 N/100mm (16 - 18 oz.)</b>
Tensile	<b>297 N/100mm (17lb./in)</b>
Elongation	<b>3-4%</b>
Tear Resistance	<b>50</b>
Shelf Life**	<b>1 year</b>

\* Adhesion PSTC-1, 1 minute on stainless steel at time of manufacture.

\*\* Stored at 22°C (72°F)/50-55 % RH

### FEATURES

- Removes easily following graphics application.
- If adhesive touches adhesive, Conform pulls apart easily with no adhesive delamination.
- Works well in either wet or dry applications with no adhesive transfer.

### APPLICATIONS

- Premask for small and medium size vinyl graphics.
- All-purpose application tape for wet and dry applications.
- Excellent for transferring graphics to banners.

### WARRANTY

Tapes are only warranted to be free of defect in workmanship or materials at time of shipment. Manufacturer will replace or credit any material manufacturer deems defective. No acceptance or responsibility for loss, damage, or expense, implies or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability herewith.



**RTape Corp.**  
6 Ingersoll Road  
South Plainfield, NJ 07080  
T 1-800-440-1250  
www.rtape.com

**RESPONSIVE  
RELIABLE  
RESOURCEFUL**