



ARLON

SLX™ CAST WRAP + FLITE™ TECHNOLOGY

It's Not Just Air Egress, It's Better!

SLX™ Cast Wrap is a premium gloss white repositionable cast film with FLITE Technology™. Designed for the single installer, this film allows for a fast wrap and superior repositionability for full and partial, vehicle and fleet applications. FLITE Technology™ is a lite contact system allowing graphics to float over a substrate until firm pressure is applied. It guarantees the fastest installation while ensuring long-term bond, conforming effortlessly around rivets, complex curves and deep channels. SLX Cast Wrap offers a vibrant and reliable print quality which is present across Eco-Solvent, Solvent, Latex and UV print systems. Arlon strongly recommends the use of Series 3270 Overlamine when using SLX Cast Wrap for optimum performance of the film.

Unique Features:

- ▶ Lite Initial Contact with Air Egress for Superior Repositionability
- ▶ Fast Wraps with One Installer
- ▶ Vibrant and Reliable Print Quality

Applications:

- ▶ Vehicle Graphics (Full, Partial)
- ▶ Vehicle Decals
- ▶ Fleet Graphics



Certified for HP Latex Inks

Performance & Physical Data

	SLX™ Cast Wrap	Series 3270 Overlamine
Finish:	Gloss	Gloss
Film Life (Unprinted):	7 Years	7 Years
Roll Widths:	30" (0,76 m) 48" (1,22 m) 54" (1,37 m) 60" (1,52 m)	30" (0,76 m) 48" (1,22 m) 54" (1,37 m) 60" (1,52 m)
Roll Lengths:	50 yards (45,72 m)	50 yards (45,72 m)
Adhesive:	Clean Removing, Repositionable (Light Gray)	Permanent (Clear)
Release Liner:	Lay-Flat Polycoated with Low Profile FLITE Technology™	Clay Coated
Compatible Ink:	Eco-Solvent Solvent UV Latex	N/A

USA: a 200 Boysenberry Lane, Placentia, CA 92870, USA
 EUROPE: a North Sea Building, Gevers Deynootweg 93, 4th Floor, 2586BK Den Haag, The Netherlands
 UK: a P6 Parklands, Heywood Distribution Park, Heywood, Lancashire OL102TT, UK

p 800 232 7161 / 714 985 6300 f 800 329 2756
 p +31 0 70 354 4311 f +31 0 70 355 7721
 p +44 0 161 884 0592 f +31 0 70 355 7721

arlon.com