



ASPHALT ART

THE SOLUTION FOR OUTDOOR COMMUNICATION

AsphaltArt is designed to be used for short to mid term applications dependent on where the product is applied. The product can be used on surfaces such as asphalt, cement and untreated stone, pavement and many more surfaces.

The material can easily be removed from such surfaces. AsphaltArt is designed to be very robust against abrasion and other influences caused by normal use of the product. The special adhesive is designed to work outdoor on rough surfaces.

Uses

- Shop entries & stairways
- Bus, tramway or metro stations, airports
- Sport events: Motor sport events, marathons etc
- Car, motorbike & general vehicle resellers
- Museums, meetings and other cultural events
- Petrol stations
- Car parks - indoor and outdoor including driveways
- Fast food drive through
- Sports stadiums
- Pedestrian areas

Features & Benefits

- High visual impact
- Easy to apply and remove
- Suitable for rough surfaces
- Slip resistant
- PVC free





ASPHALT ART

THE SOLUTION FOR OUTDOOR COMMUNICATION

Durability

The durability of AsphaltArt is dependent on the way the product has been applied – especially also on how it has been adjusted to uneven surfaces as well as on the surface in general on where it has been applied. We recommend a maximum use of 1–6 months. Furthermore, it also depends on the mechanical use of the surface where it is applied.

Storage

Shelf life is 12 months from the date of delivery. Storage conditions (15 – 24° C - humidity between 40 and 65 % RH).

Warranty

The product has been used in many places under all possible conditions and has proven its reliability and performance. Since there are endless possibilities on how and where the product is going to be applied all product warranty automatically ends as soon as the liner is removed.

Printing method

The material can be colour printed with UV curable inks.

Recycle

AsphaltArt is designed to be fully recyclable. Used material and production waste can be handled as “aluminum waste”.

Technical information

Size	Width: 1.22 m	Length: 30.48 m	
Material	Coated soft aluminum (polyurethane)		220μ +/- 10μ
Adhesive	Permanent acrylic solvent		80μ +/- 5μ
	Total weight		428 g/m²
Certificates	Surfaces roughness (SRT)		55
	Slip-resistance		R11 / BS7976
	Flame resistance		M1 / F2
Application	minimum application temperature		+10°C / +50°F

Peel Adhesion to:	Stainless Steel	Polyethylene	Powder coated surfaces *
15 minute dwell	80oz/in (88N/100 mm)	50oz/in (55N/100mm)	70oz/in (77N/100mm)
24 hours dwell	100oz/in (110N/100 mm)	60oz/in (66N/100 mm)	80oz/in (88N/100 mm)

Chemical resistance

Water	R	Diesel Fuel	R
10% Salt Water	R	Hydraulic Fluid	R
Bleach	R	50% Anti-freeze in water	R
Trichloroethylene	NR	Methyl Ethyl Ketone	NR
25% Sulphuric Acid	I	Mineral Spirits	R
1% Sodium Hydroxide	I	99% IPA	R
Gasoline unleaded	R		

R = recommended for non continuous immersion
I = recommended for intermittent exposure only
NR = not recommended