

SF100- Conform Chrome Series Films are chrome accent films designed to add special effects to graphics. Before using, user shall determine the suitability of the product for its intended use and accepts responsibility to ensure compliance with any and all laws and regulations concerning the use of chrome film on vehicles or in the ultimate graphic application, end user assumes all risk and liability in connection therewith.

DO NOT OVERHEAT OR OVERSTRETCH GRAPHICS DURING APPLICATION. IF TOO MUCH HEAT OR STRETCH IS USED THE FILM WILL WHITEN AND THERE IS NO WARRANTY FOR WHITENING OF FILM DURING APPLICATION.

To minimize scratching during application, and during the life of the graphic, it is recommended that the convertor protects the film with the use of DOL1460. The DOL1460 laminated to the top of the film prior to application provides greater structure to the product, and improves abrasion resistance. However, greater care should be taken to ensure proper conformability for the end use application.

Some surface imperfections are not uncommon in the film, these are not considered a defect.

Please refer to appropriate Product Data Sheet, and Instructional Bulletins for additional information, available at www.averygraphics.com, your Avery Dennison authorized distributor, or Avery Dennison representative.



Inspired Brands.
Intelligent World.™

SF100- Conform Chrome Series Films are chrome accent films designed to add special effects to graphics. Before using, user shall determine the suitability of the product for its intended use and accepts responsibility to ensure compliance with any and all laws and regulations concerning the use of chrome film on vehicles or in the ultimate graphic application, end user assumes all risk and liability in connection therewith.

DO NOT OVERHEAT OR OVERSTRETCH GRAPHICS DURING APPLICATION. IF TOO MUCH HEAT OR STRETCH IS USED THE FILM WILL WHITEN AND THERE IS NO WARRANTY FOR WHITENING OF FILM DURING APPLICATION.

To minimize scratching during application, and during the life of the graphic, it is recommended that the convertor protects the film with the use of DOL1460. The DOL1460 laminated to the top of the film prior to application provides greater structure to the product, and improves abrasion resistance. However, greater care should be taken to ensure proper conformability for the end use application.

Some surface imperfections are not uncommon in the film, these are not considered a defect.

Please refer to appropriate Product Data Sheet, and Instructional Bulletins for additional information, available at www.averygraphics.com, your Avery Dennison authorized distributor, or Avery Dennison representative.



Inspired Brands.
Intelligent World.™