

Removable Wall Film

This removable wall film is a 6 mil matter white vinyl film coated with a removable acrylic based adhesive. This film is printable with Solvent, Eco-Solvent, Latex and UV printers and works well on low VOC paints. The material can be repositioned easily for an easy professional looking installation, everytime! Learn more at www.fellers.com/fellers-black-label.

Product Description	Removable Wall Film
Film	
Film Type	White Calendered Vinyl
Film Thickness (mils) ASTM-D 1593	6 mil (± 150um)
Gloss (60°)	≤20
Opacity (%) with adhesive	98
Adhesive	
Adhesive Type	Acrylic
Adhesive Thickness (microns)	0.9 / (23 μm)
Adhesive Color	Clear
Elongation (%)	MD > 130 / CD > 200
Dimensional Stability (% Shrinkage) FTM 14	MD < 0.20 mm / CD < 0.20 mm
Peel Strength on Stainless Steel: 15 min typical value (lbs/in / N/25m)	.8 / 4
Peel Strength on Stainless Steel: 24 hrs typical value (lbs/in / N/25m)	1.2 / 5.4
Liner	
Liner Weight (# / (g/m ²))	90 / 145
Liner Type	Double-sided PE Coated Kraft
Release Force @ 300" / min (g/2") ASTM D-1000	Medium
Performance Guidance	
Application Temperature	± >40 °F
Service Temperature	-40 °F to 195 °F
Shelf Life	1 year
Storage Temp / Rel. Humidity	70 °F / 50%
Outdoor Durability	N/A (5 years Indoor)
Printers	Eco-Solvent, Solvent, Latex, UV
Suggested Uses:	<ul style="list-style-type: none"> Indoor Decals Walls General Signage
Installation and Conversion:	<ul style="list-style-type: none"> Dry Apply Die Cuttable Flat Bed Cuttable
Approved Surfaces:	<ul style="list-style-type: none"> Smooth Painted Walls

For best results, printed graphics using solvent based inks should always be allowed to outgas for 24-48 hrs before installation or lamination. Designed for temporary applications. Painted walls must be fully cured (90) prior to installation.

ASTM E84 Class 1 or A (standard test method for surface burning characteristics in building materials)

Disclaimer

All data provided in this document is based upon tests executed by Fellers or their manufacturing partners and determined to be reliable information. Results may represent an average and any minimum or maximum values provided should be considered as a recommendation based on average circumstances. In the end, it is up to the end user to determine at their risk if the product is right for the desired application and outcome. These settings do not provide or imply a guarantee of the products use, outdoor durability, removability, or printability. In general, non-vertical applications can result in a reduced performance of 50% or more. This information is subject to change at any time without notice.

