

Clear Static Cling

The Fellers Black Label static cling is an extremely flexible film great for temporary graphics in residential or commercial applications. The 7 mil clear film has excellent printability offering a unique transparency to the print. This film is adhesive free utilizing the plasticizers in the film to adhere to high energy surfaces such as smooth glass or acrylic. Visit www.fellers.com for more information.

Product Description	Clear Static Cling
Film	
Film Type	Clear Static Cling
Film Thickness (microns)	7 mil / 180 µm
Gloss	>60
Liner	
Liner Weight (# per ream) / (g/m ²)	90 / 145
Liner Type	Double-sided PE Coated Kraft
Liner Release	Medium
Performance Guidance	
Application Temperature	>40 °F
Service Temperature	20 °F to 195 °F
Shelf Life	6 months
Storage Temp / Rel. Humidity	70 °F / 50%
Outdoor Durability	3 months
Printers	Eco-Solvent, Solvent, Latex, UV
Suggested Uses:	<ul style="list-style-type: none"> Indoor/Outdoor Retail Window Displays General Signage
Installation and Conversion:	<ul style="list-style-type: none"> Wet or Dry Apply Die Cuttable Flat Bed Cuttable
Approved Surfaces:	<ul style="list-style-type: none"> Flat Glass Acrylic Vehicle Windows (Subject to local laws & regulations)
Improper storage conditions may result in plasticiser migration which will affect printability. Please follow storage guidelines for best results.	
For best results, printed graphics using solvent based inks should always be allowed to outgas for 24-48 hrs before installation or lamination. Designed for temporary applications. Painted walls must be fully cured (90) prior to installation.	
ASTM E84 Class 1 or A (standard test method for surface burning characteristics in building materials)	

Terms & Conditions

All data provided in this document is based upon tests executed by Fellers or their manufacturing partners and determined to be reliable information. Results may represent an average and any minimum or maximum values provided should be considered as a recommendation based on average circumstances. In the end, it is up to the end user to determine at their risk if the product is right for the desired application and outcome. These settings do not provide or imply a guarantee of the products use, outdoor durability, removability, or printability. In general, non-vertical applications can result in a reduced performance of 50% or more. This information is subject to change at any time without notice.

Disclaimer

All data provided in this document is based upon tests executed by Fellers or their manufacturing partners and determined to be reliable information. Results may represent an average and any minimum or maximum values provided should be considered as a recommendation based on average circumstances. In the end, it is up to the end user to determine at their risk if the product is right for the desired application and outcome. These settings do not provide or imply a guarantee of the products use, outdoor durability, removability, or printability. In general, non-vertical applications can result in a reduced performance of 50% or more. This information is subject to change at any time without notice.

