

Paint Mask

Fellers Black Paint Mask is a polymeric-blend vinyl paint mask, specially-designed for making plotter-cut stencils for painted graphics. Our mask removes easily and cleanly from most factory paint surfaces without leaving any adhesive residue or other surface contamination. For trouble-free results, remove stencils immediately after painting and curing. Choose between Matte White or Yellow mask.

Product Description	Paint Mask
Film	
Film Type	3.2 mil (80 microns) polymeric-blend calendered
Film Thickness (microns)	3.2 mil (86 µm)
Gloss	≥ 22
Opacity (%) with adhesive	94
Adhesive	
Adhesive Type	Clear Removable
Adhesive Thickness (microns)	1 mil / 25
Adhesive Color	Clear
Elongation (%)	MD > 90 / CD > 150
Dimensional Stability (% Shrinkage) FTM 14	MD < 0.20 mm / CD < 0.10 mm
Liner	
Liner Weight (# per ream) / (g/m ²)	78 / 127
Liner Type	White Kraft Liner
Liner Release	High
Performance Guidance	
Application Temperature	- 40 °F to 176 °F
Service Temperature	Baking Cycles up to 110 °F (Yellow Version Only)
Shelf Life	1 year
Storage Temp / Rel. Humidity	70 °F / 50%
Outdoor Durability	N/A
Suggested Uses:	<ul style="list-style-type: none"> Indoor Paint Mask
Installation and Conversion:	<ul style="list-style-type: none"> Dry Apply Die Cuttable Flat Bed Cuttable
Approved Surfaces:	<ul style="list-style-type: none"> Painted Metal Glass Smooth Surfaces Acrylic

After removing the application tape from any paint mask, always re-squeegee the entire vinyl graphic. This application step ensures crisp edges of painted graphics and prevents paint seepage under any unsecure edge. Under normal storage conditions. 70 degrees F 50% relative humidity. Not recommended for vehicle windows. Resists mild acids, alkalis and salt solutions. Not intended for screen print applications

Terms & Conditions

All data provided in this document is based upon tests executed by Fellers or their manufacturing partners and determined to be reliable information. Results may represent an average and any minimum or maximum values provided should be considered as a recommendation based on average circumstances. In the end, it is up to the end user to determine at their risk if the product is right for the desired application and outcome. These settings do not provide or imply a guarantee of the products use, outdoor durability, removability, or printability. In general, non-vertical applications can result in a reduced performance of 50% or more. This information is subject to change at any time without notice.

Disclaimer

All data provided in this document is based upon tests executed by Fellers or their manufacturing partners and determined to be reliable information. Results may represent an average and any minimum or maximum values provided should be considered as a recommendation based on average circumstances. In the end, it is up to the end user to determine at their risk if the product is right for the desired application and outcome. These settings do not provide or imply a guarantee of the products use, outdoor durability, removability, or printability. In general, non-vertical applications can result in a reduced performance of 50% or more. This information is subject to change at any time without notice.

