

Textured Overlaminates

Fellers Black Label Textured Laminates provide enhanced protection for graphics installed in high traffic areas. These laminates offer a textured face for additional wear protection and non-slip as well as adding a unique aesthetic upgrade. The rugged design is offered in 4, 6 or 10 mil options to fit any lamination requirements necessary.

Product Description	Textured Overlamine
Film	
Film Type	Clear Textured PVC
Film Thickness (microns)	4, 6, 10 mil
Gloss	≤ 90
Opacity (%) with adhesive	N/A
Adhesive	
Adhesive Type	Solvent
Adhesive Thickness (microns)	1.18 mil / 30 (+ / - .01%)
Adhesive Color	Clear
Elongation (%)	MD ≤ 150
Dimensional Stability (% Shrinkage) FTM 14	0.010"
Peel Strength on Stainless Steel: 15 min typical value (lbs/in / N/25m)	1.2 / 6.85
Peel Strength on Stainless Steel: 24 hrs typical value (lbs/in / N/25m)	1.4 / 7.99
Liner	
Liner Type	Clear PET
Liner Release	High
Performance Guidance	
Application Temperature	≥ +40 °F
Service Temperature	-22 °F to 176 °F
Shelf Life	1 year
Storage Temp / Rel. Humidity	70 °F / 50%
Printers	N/A
Heat assist recommended. Do not exceed 100 °F.	
Suggested Uses:	<ul style="list-style-type: none"> • Interior Countertop Graphics • Smooth Interior Floor • General Signage • POP/Retail
Installation and Conversion:	<ul style="list-style-type: none"> • Dry Apply • Heat Assist Recommended
Under normal storage conditions. 70 degrees F 50% relative humidity. Not recommended for vehicle windows. Resists mild acids, alkalis and salt solutions. Not intended for screen print applications.	

Disclaimer

All data provided in this document is based upon tests executed by Fellers or their manufacturing partners and determined to be reliable information. Results may represent an average and any minimum or maximum values provided should be considered as a recommendation based on average circumstances. In the end, it is up to the end user to determine at their risk if the product is right for the desired application and outcome. These settings do not provide or imply a guarantee of the products use, outdoor durability, removability, or printability. In general, non-vertical applications can result in a reduced performance of 50% or more. This information is subject to change at any time without notice.

