

# White Static Cling

The Fellers Black Label white static cling is an extremely flexible film great for temporary graphics in residential or commercial applications. The 7 mil white film offers excellent printability with a high opacity for vibrant prints. This film is adhesive free utilizing the plasticizers in the film to adhere to high energy surfaces such as smooth glass or acrylic. Visit [www.fellers.com](http://www.fellers.com) for more information.

Product Description	White Static Cling
<b>Film</b>	
Film Type	White Static Cling
Film Thickness (microns)	7 mil / 180 µm
Gloss	>90
Opacity (%)	96
Elongation (%)	MD > 300 / CD > 300
Dimensional Stability (% Shrinkage) FTM 14	N/A
<b>Liner</b>	
Liner Weight (# per ream) / (g/m <sup>2</sup> )	90 / 145
Liner Type	Double-sided PE Coated Kraft
Liner Release	Medium
<b>Performance Guidance</b>	
Application Temperature	>40 °F
Service Temperature	-40 °F to 195 °F
Shelf Life	6 months
Storage Temp / Rel. Humidity	70 °F / 50%
Outdoor Durability	3 months
Printers	Eco-Solvent, Solvent, Latex, UV
Suggested Uses:	<ul style="list-style-type: none"> <li>Indoor/Outdoor</li> <li>Retail Window Displays</li> <li>General Signage</li> </ul>
Installation and Conversion:	<ul style="list-style-type: none"> <li>Wet or Dry Apply</li> <li>Die Cuttable</li> <li>Flat Bed Cuttable</li> </ul>
Approved Surfaces:	<ul style="list-style-type: none"> <li>Flat Glass</li> <li>Acrylic</li> <li>Vehicle Windows (Subject to local laws &amp; regulations)</li> </ul>
<p>Improper storage conditions may result in plasticiser migration which will affect printability. Please follow storage guidelines for best results.</p> <p>For best results, printed graphics using solvent based inks should always be allowed to outgas for 24-48 hrs before installation or lamination. Designed for temporary applications. Painted walls must be fully cured (90) prior to installation.</p> <p><b>ASTM E84 Class 1 or A</b> (standard test method for surface burning characteristics in building materials)</p>	

**Disclaimer**

All data provided in this document is based upon tests executed by Fellers or their manufacturing partners and determined to be reliable information. Results may represent an average and any minimum or maximum values provided should be considered as a recommendation based on average circumstances. In the end, it is up to the end user to determine at their risk if the product is right for the desired application and outcome. These settings do not provide or imply a guarantee of the products use, outdoor durability, removability, or printability. In general, non-vertical applications can result in a reduced performance of 50% or more. This information is subject to change at any time without notice.

