

6 Mil Economy Perf 70/30

This economy grade window perf has a 70/30 perforated pattern for maximum printable surface area. Great for applications requiring an outdoor life expectancy of 12 months or less. The dual perforated liner allows for easy printing across all popular print platforms without clogging perforations with ink. The black back allows for easy viewing from the backside of the film when applied to windows. Available in 54" or 60" widths in 100' lengths.

Product Description	Economy Window Perf 70/30
Film	
Film Type	White/Black
Film Thickness (mil/microns)	6 mil (160 µm)
Gloss	>75
Opacity (%) with adhesive	100
Dimensional Stability MD FTM 14	≤ 0.5 mm
Dimensional Stability CD FTM 14	≤ 0.4 mm
Adhesive	
Adhesive Type	Solvent
Adhesive Thickness (microns)	0.9 / (23 µm)
Adhesive Color	Clear
Liner	
Liner Weight (# per ream) / (g/m ²)	135 / 200
Liner Type	Perforated double PE liner laminated to PE Coated Kraft
Liner Release	High
Performance Guidance	
Application Temperature	>40 °F
Service Temperature	-4 °F to 158 °F
Storage Temp / Rel. Humidity	70 °F / 50%
Outdoor Durability	Up to 12 months ²
Printers	Eco-Solvent, Solvent, Latex, UV
Suggested Uses:	<ul style="list-style-type: none"> Indoor/Outdoor Retail Window Displays General Signage
Installation and Conversion:	<ul style="list-style-type: none"> Dry Apply Die Cuttable Flat Bed Cuttable
Approved Surfaces:	<ul style="list-style-type: none"> Flat Glass Acrylic
² Under normal storage conditions. 70 °F / 50% relative humidity	
Not recommended for vehicle windows	

Terms & Conditions

All statements, information and recommendations published by Fellers, LLC are based on tests that were believed to be conducted with reliable and accurate equipment. The result of any test or information provided is not a guarantee and Fellers, LLC makes no warranty based on this information. Should a problem arise with the product, please reach out to customer service or your local Fellers, LLC sales rep for assistance. Fellers, LLC will make every attempt to satisfy proven fault or failure in a product, up to replacement of the product with an equal or like product not to exceed the original unit value paid at the time of purchase. The replacement will be at the discretion of Fellers, LLC and will be limited to the actual defective product and shall not exceed the original qty purchased. Fellers, LLC shall not be liable for injury, loss or damage, direct or indirect, related to the use or the inability to use the product. Nor shall Fellers, LLC be liable for any costs or expenses incurred in the processing or printing on the product. It is the responsibility of the user to ensure the product is suitable for the intended application. User assumes all risk associated with the product, its installation and all risks associated with it. No statements or recommendations other than those contained in the technical information published by Fellers, LLC shall have force or effect, unless otherwise obtained in a written document physically signed by an officer of Fellers, LLC.

Disclaimer

All data provided in this document is based upon tests executed by Fellers or their manufacturing partners and determined to be reliable information. Results may represent an average and any minimum or maximum values provided should be considered as a recommendation based on average circumstances. In the end, it is up to the end user to determine at their risk if the product is right for the desired application and outcome. These settings do not provide or imply a guarantee of the products use, outdoor durability, removability, or printability. In general, non-vertical applications can result in a reduced performance of 50% or more. This information is subject to change at any time without notice.

