



ARLON

FUSION WRAP + FLITE[®] TECHNOLOGY

Specifying the right product could be the difference between bidding on or winning a job. Fusion Wrap featuring FLITE Technology[®] can be the product of choice in various situations: when cost-driven opportunities are presented, if shorter to medium term durability is specified, or when a flat to simple curve vehicle wrap application is present. A calendared film specifically designed for vehicle wraps, the thin and flexible film facilitates ease of use and efficiency. The lite initial contact adhesive system from FLITE Technology[®] will ensure repositionability, developing a quick anchor tack to speed up installations. Pair with Series 3170 intermediate cast overlaminates for the thinnest hybrid installation.

Unique Features:

- ▶ Product of Choice in Cost-Driven Opportunities
- ▶ Thin, Flexible, High-Performance Calendared Film Facilitating Easier Handling and Installation
- ▶ Clean Removability up to 2 Years on Most Vehicle Wrap Applications
- ▶ Added Repositionability During Installation Building a Quick Bond
- ▶ Superior Conformability and Stretch for a Calendared Wrap Film

Applications:

- ▶ Vehicle Wraps

Performance & Physical Data	
Finish:	Gloss
Durability (Unprinted):	7 Years
Roll Widths:	54" (1,37 m) 60" (1,52 m)
Roll Lengths:	50 Yards (45,72 m)
Adhesive:	Clean Removing, Repositionable (Light Gray)
Release Liner:	Lay-Flat Polycoated with Low Profile FLITE Technology [®]
Ink Compatibility:	Eco-Solvent Solvent UV Latex
Compatible Overlaminates:	Series 3170 Series 3220 Series 3270 Series 3210 Series 3420*

*Use on flat and simple curves only
To ensure as successful vehicle wrap application, please read through Arlon's Fusion Wrap Installation Guide



Certified for HP Latex Inks

USA

- a 200 Boysenberry Lane, Placentia, CA 92870
- p 800 232 7161 / +1 714 985 6300
- f +1 714 985 6305

EUROPE

- a Dr. Lelykade 22B, 2583CM Den Haag, The Netherlands
- p +31 70 354 4311
- f +31 70 355 7721

CHINA

- a No. 1989 Xinchang Road, Weifang, Shandong, 262400
- p +86 0536 6226568